



REQUEST ORDER:	2509	SITE CONTACT NAME:	Jason Hilton	Are you sending in a roll for measurement?	<input type="radio"/> Yes <input checked="" type="radio"/> No																		
DISTRIBUTOR:	QCS	SITE NUMBER:		Do you need rolls back?	<input type="radio"/> Yes <input type="radio"/> No																		
SITE:	Holcim Cement Holly Hill SC	ROLL PERFORMANCE INTEREST:		If yes, where?																			
CONVEYOR NUMBER:	Quarry	<input checked="" type="checkbox"/> WEAR LIFE	<input type="checkbox"/> NOISE																				
ROLL MANUFACTURER:		<input type="checkbox"/> WEIGHT	<input type="checkbox"/> RECYCLABILITY																				
FRAME MANUFACTURER:		<input type="checkbox"/> POWER CONSUMPTION	<input checked="" type="checkbox"/> CORROSION																				
BELT WIDTH:	IN. 48      MM	ROLL LOCATION: (Select one)																					
BELT SPEED:		<input type="radio"/> EQUAL TROUGH <input type="radio"/> CENTER TROUGH <input type="radio"/> WING TROUGH <input type="radio"/> FLAT RETURN <input checked="" type="radio"/> VEE RETURN																					
TONS PER HOUR:		ROLL CEMA RATING: (Select one)		<input type="radio"/> B <input type="radio"/> C <input checked="" type="radio"/> D <input type="radio"/> E <input type="radio"/> F																			
ROLLER DIMENSIONS:		FRAME TROUGHING ANGLE: (Select one)		<input type="radio"/> 20% <input type="radio"/> 35% <input type="radio"/> 45% <input type="radio"/> OTHER																			
<table border="1"> <thead> <tr> <th></th> <th>INCHES</th> <th>MILLIMETERS</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>23-9/16</td> <td></td> </tr> <tr> <td>2</td> <td></td> <td></td> </tr> <tr> <td>3</td> <td>26-9/16</td> <td></td> </tr> <tr> <td>4</td> <td></td> <td>30</td> </tr> <tr> <td>5</td> <td>5</td> <td></td> </tr> </tbody> </table>			INCHES	MILLIMETERS	1	23-9/16		2			3	26-9/16		4		30	5	5				ROLLER OPERATING TEMPERATURE RANGE <input type="radio"/> Less than -22°F (-30°C) <input checked="" type="radio"/> Between -22°F (-30°C) and 140°F (60°C) <input type="radio"/> Above 140°F (60°C)	
	INCHES	MILLIMETERS																					
1	23-9/16																						
2																							
3	26-9/16																						
4		30																					
5	5																						
		SPACING BETWEEN FRAMES																					
		MATERIAL CONVEYED		limestone																			
		LENGTH OF TRIAL/TEST		ROLL QUANTITY	20																		

SHAFT END DETAILS—TYPE: (Select one)		
<input type="radio"/> A <input type="radio"/> B <input type="radio"/> C <input type="radio"/> D <input type="radio"/> F <input checked="" type="radio"/> G <input type="radio"/> H <input type="radio"/> J <input type="radio"/> K <input type="radio"/> L		
DIMENSIONS	INCHES	MILLIMETERS
F		
G		
H		
I		
J		
<p><b>TYPE—D</b></p>		
<p><b>TYPE—J</b></p>		
<p><b>TYPE—A</b></p>		
<p><b>TYPE—F</b></p>		
<p><b>TYPE—K</b></p>		
<p><b>TYPE—B</b></p> <p>Note interior hex</p>		
<p><b>TYPE—G</b></p>		
<p><b>TYPE—L</b></p> <p>Note interior round</p>		
<p><b>TYPE—C</b></p> <p>G THREAD</p>		
<p><b>TYPE—H</b></p>		
NOTES The shaft has 2 flats, that are 15.3mm across (I have pictures that I will email to Bill B.) There is a hole drilled thru the shaft, 9mm diameter, center of hole is 42.5mm from the roll end of the shaft		