



REQUEST ORDER:	2612	SITE CONTACT NAME:	Gabe Meehan	Are you sending in a roll for measurement?	<input type="radio"/> Yes <input checked="" type="radio"/> No																		
DISTRIBUTOR:	QCS - VaMN	SITE NUMBER:	218.578.0966	Do you need rolls back?	<input type="radio"/> Yes <input checked="" type="radio"/> No																		
SITE:	Cleveland Cliffs - Thunderbird	ROLL PERFORMANCE INTEREST:	If yes, where?																				
CONVEYOR NUMBER:	POC	<input checked="" type="checkbox"/> WEAR LIFE	<input type="checkbox"/> NOISE																				
ROLL MANUFACTURER:	PPI	<input checked="" type="checkbox"/> WEIGHT	<input type="checkbox"/> RECYCLABILITY																				
FRAME MANUFACTURER:	PPI	<input type="checkbox"/> POWER CONSUMPTION	<input checked="" type="checkbox"/> CORROSION																				
BELT WIDTH:	IN. 60 MM	ROLL LOCATION: (Select one)	<input type="radio"/> EQUAL TROUGH <input type="radio"/> CENTER TROUGH <input type="radio"/> WING TROUGH <input checked="" type="radio"/> FLAT RETURN <input type="radio"/> VEE RETURN																				
BELT SPEED:		ROLL CEMA RATING: (Select one)	<input type="radio"/> B <input type="radio"/> C <input type="radio"/> D <input checked="" type="radio"/> E <input type="radio"/> F																				
TONS PER HOUR:		FRAME TROUGHING ANGLE: (Select one)	<input type="radio"/> 20% <input type="radio"/> 35% <input type="radio"/> 45% <input type="radio"/> OTHER																				
ROLLER DIMENSIONS:		ROLLER OPERATING TEMPERATURE RANGE	<input type="radio"/> Less than -22°F (-30°C) <input checked="" type="radio"/> Between -22°F (-30°C) and 140°F (60°C) <input type="radio"/> Above 140°F (60°C)																				
<table border="1"> <thead> <tr> <th></th> <th>INCHES</th> <th>MILLIMETERS</th> </tr> </thead> <tbody> <tr><td>1</td><td>62.000</td><td>1574.8</td></tr> <tr><td>2</td><td>62.250</td><td>1581.15</td></tr> <tr><td>3</td><td>66.000</td><td>1676.4</td></tr> <tr><td>4</td><td>1.125</td><td>28.575</td></tr> <tr><td>5</td><td>7.000</td><td>177.80</td></tr> </tbody> </table>			INCHES	MILLIMETERS	1	62.000	1574.8	2	62.250	1581.15	3	66.000	1676.4	4	1.125	28.575	5	7.000	177.80			SPACING BETWEEN FRAMES	
	INCHES	MILLIMETERS																					
1	62.000	1574.8																					
2	62.250	1581.15																					
3	66.000	1676.4																					
4	1.125	28.575																					
5	7.000	177.80																					
		MATERIAL CONVEYED																					
		LENGTH OF TRIAL/TEST		ROLL QUANTITY	50																		

SHAFT END DETAILS—TYPE: (Select one)		
<input type="radio"/> A <input checked="" type="radio"/> B <input type="radio"/> C <input type="radio"/> D <input type="radio"/> F <input type="radio"/> G <input type="radio"/> H <input type="radio"/> J <input type="radio"/> K <input type="radio"/> L		
DIMENSIONS	INCHES	MILLIMETERS
F		
G		
H		
I		
J		
<p>TYPE—A</p>		
<p>TYPE—B</p>		
<p>TYPE—C</p>		
<p>TYPE—D</p>		
<p>TYPE—E</p>		
<p>TYPE—F</p>		
<p>TYPE—G</p>		
<p>TYPE—H</p>		
<p>TYPE—J</p>		
<p>TYPE—K</p>		
<p>TYPE—L</p>		
NOTES		