



REQUEST ORDER:	2670	SITE CONTACT NAME:	USS - Minntac	Are you sending in a roll for measurement?	<input type="radio"/> Yes <input checked="" type="radio"/> No																		
DISTRIBUTOR:	QCS	SITE NUMBER:	218.578.0966	Do you need rolls back?	<input type="radio"/> Yes <input checked="" type="radio"/> No																		
SITE:	Virginia, MN	ROLL PERFORMANCE INTEREST:	If yes, where?																				
CONVEYOR NUMBER:	101	<input checked="" type="checkbox"/> WEAR LIFE	<input type="checkbox"/> NOISE																				
ROLL MANUFACTURER:	Superior	<input checked="" type="checkbox"/> WEIGHT	<input type="checkbox"/> RECYCLABILITY																				
FRAME MANUFACTURER:	Superior	<input type="checkbox"/> POWER CONSUMPTION	<input checked="" type="checkbox"/> CORROSION																				
BELT WIDTH:	IN. 60 MM	ROLL LOCATION: (Select one)	<input checked="" type="radio"/> EQUAL TROUGH <input type="radio"/> CENTER TROUGH <input type="radio"/> WING TROUGH <input type="radio"/> FLAT RETURN <input type="radio"/> VEE RETURN																				
BELT SPEED:		ROLL CEMA RATING: (Select one)	<input type="radio"/> B <input type="radio"/> C <input type="radio"/> D <input type="radio"/> E <input checked="" type="radio"/> F																				
TONS PER HOUR:		FRAME TROUGHING ANGLE: (Select one)	<input type="radio"/> 20% <input checked="" type="radio"/> 35% <input type="radio"/> 45% <input type="radio"/> OTHER																				
ROLLER DIMENSIONS:		ROLLER OPERATING TEMPERATURE RANGE	<input type="radio"/> Less than -22°F (-30°C) <input checked="" type="radio"/> Between -22°F (-30°C) and 140°F (60°C) <input type="radio"/> Above 140°F (60°C)																				
<table border="1"> <thead> <tr> <th></th> <th>INCHES</th> <th>MILLIMETERS</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>21.750</td> <td>552.45</td> </tr> <tr> <td>2</td> <td>22.000</td> <td>558.80</td> </tr> <tr> <td>3</td> <td>23.437</td> <td>595.3125</td> </tr> <tr> <td>4</td> <td>1.158</td> <td>29.4132</td> </tr> <tr> <td>5</td> <td>7.00</td> <td>177.80</td> </tr> </tbody> </table>			INCHES	MILLIMETERS	1	21.750	552.45	2	22.000	558.80	3	23.437	595.3125	4	1.158	29.4132	5	7.00	177.80			SPACING BETWEEN FRAMES	48"
			INCHES	MILLIMETERS																			
		1	21.750	552.45																			
		2	22.000	558.80																			
		3	23.437	595.3125																			
4	1.158	29.4132																					
5	7.00	177.80																					
		MATERIAL CONVEYED	TACONITE																				
		LENGTH OF TRIAL/TEST		ROLL QUANTITY	100																		

SHAFT END DETAILS—TYPE: (Select one)																				
<input type="radio"/> A <input checked="" type="radio"/> B <input type="radio"/> C <input type="radio"/> D <input type="radio"/> F <input type="radio"/> G <input type="radio"/> H <input type="radio"/> J <input type="radio"/> K <input type="radio"/> L																				
<table border="1"> <thead> <tr> <th>DIMENSIONS</th> <th>INCHES</th> <th>MILLIMETERS</th> </tr> </thead> <tbody> <tr> <td>F</td> <td>.379</td> <td>9.6266</td> </tr> <tr> <td>G</td> <td>.270</td> <td>6.858</td> </tr> <tr> <td>H</td> <td>1.797</td> <td>45.6438</td> </tr> <tr> <td>I</td> <td>2.000</td> <td>50.8</td> </tr> <tr> <td>J</td> <td>1.193</td> <td>30.3022</td> </tr> </tbody> </table>			DIMENSIONS	INCHES	MILLIMETERS	F	.379	9.6266	G	.270	6.858	H	1.797	45.6438	I	2.000	50.8	J	1.193	30.3022
DIMENSIONS	INCHES	MILLIMETERS																		
F	.379	9.6266																		
G	.270	6.858																		
H	1.797	45.6438																		
I	2.000	50.8																		
J	1.193	30.3022																		
		TYPE—A																		
		TYPE—B																		
		TYPE—C																		
		TYPE—D																		
		TYPE—E																		
		TYPE—F																		
		TYPE—G																		
		TYPE—H																		
		TYPE—J																		
		TYPE—K																		
		TYPE—L																		
NOTES This is for Gabe in MN																				