



REQUEST ORDER:	2672	SITE CONTACT NAME:	USS	Are you sending in a roll for measurement?	<input type="radio"/> Yes <input checked="" type="radio"/> No																		
DISTRIBUTOR:	QCS	SITE NUMBER:	Minntac - Crusher	Do you need rolls back?	<input type="radio"/> Yes <input type="radio"/> No																		
SITE:	Virginia, MN	ROLL PERFORMANCE INTEREST:	If yes, where?																				
CONVEYOR NUMBER:	103	<input checked="" type="checkbox"/> WEAR LIFE	<input type="checkbox"/> NOISE																				
ROLL MANUFACTURER:	Superior	<input checked="" type="checkbox"/> WEIGHT	<input type="checkbox"/> RECYCLABILITY																				
FRAME MANUFACTURER:	Superior	<input type="checkbox"/> POWER CONSUMPTION	<input checked="" type="checkbox"/> CORROSION																				
BELT WIDTH:	IN. 60 MM	ROLL LOCATION: (Select one)																					
BELT SPEED:		<input checked="" type="radio"/> EQUAL TROUGH <input type="radio"/> CENTER TROUGH <input type="radio"/> WING TROUGH <input type="radio"/> FLAT RETURN <input type="radio"/> VEE RETURN																					
TONS PER HOUR:		ROLL CEMA RATING: (Select one)		<input type="radio"/> B <input type="radio"/> C <input type="radio"/> D <input type="radio"/> E <input checked="" type="radio"/> F																			
ROLLER DIMENSIONS: <table border="1"> <thead> <tr> <th></th> <th>INCHES</th> <th>MILLIMETERS</th> </tr> </thead> <tbody> <tr><td>1</td><td>23.75</td><td>603.25</td></tr> <tr><td>2</td><td>24.00</td><td>609.6</td></tr> <tr><td>3</td><td>25.375</td><td>644.525</td></tr> <tr><td>4</td><td>1.158</td><td>29.4132</td></tr> <tr><td>5</td><td>7.00</td><td>177.8</td></tr> </tbody> </table>			INCHES	MILLIMETERS	1	23.75	603.25	2	24.00	609.6	3	25.375	644.525	4	1.158	29.4132	5	7.00	177.8	FRAME TROUGHING ANGLE: (Select one) <input type="radio"/> 20% <input checked="" type="radio"/> 35% <input type="radio"/> 45% <input type="radio"/> OTHER		ROLLER OPERATING TEMPERATURE RANGE <input type="radio"/> Less than -22°F (-30°C) <input checked="" type="radio"/> Between -22°F (-30°C) and 140°F (60°C) <input type="radio"/> Above 140°F (60°C)	
			INCHES	MILLIMETERS																			
		1	23.75	603.25																			
2	24.00	609.6																					
3	25.375	644.525																					
4	1.158	29.4132																					
5	7.00	177.8																					
SPACING BETWEEN FRAMES: 48"		MATERIAL CONVEYED: TACONITE		LENGTH OF TRIAL/TEST: _____ ROLL QUANTITY: 100																			

SHAFT END DETAILS—TYPE: (Select one)																				
<input type="radio"/> A	<input checked="" type="radio"/> B	<input type="radio"/> C																		
<input type="radio"/> D	<input type="radio"/> F	<input type="radio"/> G																		
<input type="radio"/> H	<input type="radio"/> J	<input type="radio"/> K																		
<input type="radio"/> L																				
<table border="1"> <thead> <tr> <th>DIMENSIONS</th> <th>INCHES</th> <th>MILLIMETERS</th> </tr> </thead> <tbody> <tr><td>F</td><td>.379</td><td>9.6266</td></tr> <tr><td>G</td><td>.270</td><td>6.858</td></tr> <tr><td>H</td><td>1.797</td><td>45.6438</td></tr> <tr><td>I</td><td>2.000</td><td>50.8</td></tr> <tr><td>J</td><td>1.193</td><td>30.3022</td></tr> </tbody> </table>	DIMENSIONS	INCHES	MILLIMETERS	F	.379	9.6266	G	.270	6.858	H	1.797	45.6438	I	2.000	50.8	J	1.193	30.3022	<p>TYPE—D</p>	<p>TYPE—J</p>
DIMENSIONS	INCHES	MILLIMETERS																		
F	.379	9.6266																		
G	.270	6.858																		
H	1.797	45.6438																		
I	2.000	50.8																		
J	1.193	30.3022																		
<p>TYPE—A</p>	<p>TYPE—F</p>	<p>TYPE—K</p>																		
<p>TYPE—B</p> <p>Note interior hex</p>	<p>TYPE—G</p>	<p>TYPE—L</p> <p>Note interior round</p>																		
<p>TYPE—C</p>	<p>TYPE—H</p>	<p>NOTES</p> <p>Gabe Meehan - Virginia, MN</p>																		