



REQUEST ORDER:	2674	SITE CONTACT NAME:	USS	Are you sending in a roll for measurement?	<input type="radio"/> Yes <input checked="" type="radio"/> No																		
DISTRIBUTOR:	QCS	SITE NUMBER:	Minntac - Crusher	Do you need rolls back?	<input type="radio"/> Yes <input checked="" type="radio"/> No																		
SITE:	VaMN	ROLL PERFORMANCE INTEREST:		If yes, where?																			
CONVEYOR NUMBER:	103	<input checked="" type="checkbox"/> WEAR LIFE		<input type="checkbox"/> NOISE																			
ROLL MANUFACTURER:	Superior	<input checked="" type="checkbox"/> WEIGHT		<input type="checkbox"/> RECYCLABILITY																			
FRAME MANUFACTURER:	Superior	<input type="checkbox"/> POWER CONSUMPTION		<input checked="" type="checkbox"/> CORROSION																			
BELT WIDTH:	IN. <input type="text"/> MM <input type="text"/>	ROLL LOCATION: (Select one)																					
BELT SPEED:		<input type="radio"/> EQUAL TROUGH <input type="radio"/> CENTER TROUGH <input type="radio"/> WING TROUGH <input checked="" type="radio"/> FLAT RETURN <input type="radio"/> VEE RETURN																					
TONS PER HOUR:		ROLL CEMA RATING: (Select one)		<input type="radio"/> B <input type="radio"/> C <input type="radio"/> D <input type="radio"/> E <input checked="" type="radio"/> F																			
ROLLER DIMENSIONS: <table border="1"> <thead> <tr> <th></th> <th>INCHES</th> <th>MILLIMETERS</th> </tr> </thead> <tbody> <tr><td>1</td><td>75.880</td><td>1927.352</td></tr> <tr><td>2</td><td>76.3175</td><td>1938.4645</td></tr> <tr><td>3</td><td>78.255</td><td>1987.677</td></tr> <tr><td>4</td><td>1.291</td><td>32.7914</td></tr> <tr><td>5</td><td>6.00</td><td>152.4</td></tr> </tbody> </table>			INCHES	MILLIMETERS	1	75.880	1927.352	2	76.3175	1938.4645	3	78.255	1987.677	4	1.291	32.7914	5	6.00	152.4			FRAME TROUGHING ANGLE: (Select one) <input type="radio"/> 20% <input type="radio"/> 35% <input type="radio"/> 45% <input type="radio"/> OTHER	
			INCHES	MILLIMETERS																			
		1	75.880	1927.352																			
2	76.3175	1938.4645																					
3	78.255	1987.677																					
4	1.291	32.7914																					
5	6.00	152.4																					
ROLLER OPERATING TEMPERATURE RANGE <input type="radio"/> Less than -22°F (-30°C) <input checked="" type="radio"/> Between -22°F (-30°C) and 140°F (60°C) <input type="radio"/> Above 140°F (60°C)																							
SPACING BETWEEN FRAMES: 48"																							
MATERIAL CONVEYED: Taconite																							
LENGTH OF TRIAL/TEST: <input type="text"/>		ROLL QUANTITY: 100																					

SHAFT END DETAILS—TYPE: (Select one)		
<input type="radio"/> A	<input type="radio"/> B	<input type="radio"/> C
<input type="radio"/> D	<input type="radio"/> F	<input type="radio"/> G
<input type="radio"/> H	<input type="radio"/> J	<input type="radio"/> K
<input type="radio"/> L		
TYPE—A		
TYPE—B		
TYPE—C		
TYPE—D		
TYPE—E		
TYPE—F		
TYPE—G		
TYPE—H		
TYPE—J		
TYPE—K		
TYPE—L		
NOTES Gabe Meehan - Virginia, MN		